



**Specification:**

- DC input Voltage: 24V(18V~36V)  
28V(18V~36V)
- Efficiency  $\geq 87\%$  (24Vdc @25°C, Full Load)
- Non-isolation between primary and secondary
- Low ripple & noise
- Short circuit protection
- Over load and Voltage protection
- Line regulation:  $\pm 1\%$  typical
- Load regulation:  $\pm 5\%$  typical
- Operating/storage Temp. 0°C~55°C / -40°C~ 65°C
- P/G signal delay: Power on 100~500mS; off > 1mS.
- MTBF:100K Hrs typical, at 25°C
- EMC: CE EN55022 :2006 B, EN55024 ,FCC part 15 class B
- Safety: Meet EN60950
- Dimension: W100 x H70 x D200 mm
- Cooling: 60 x 60 (mm): dual fans
- Weight: 2kgs

**2U JD2X7460**

**Output List**

Model	Input		Output min/max.A								
	Vdc	+ 5V	+3.3V	5V & 3.3V	+12V1	+12V2	+12V3	+12V1/2/3	-12V	+5VSB	Total Output
	V	A	A	W	A	A	A	W	A	A	Max(W)
<b>JD2X7460</b>	18~36	0.2/20	0.1/24	120	0.6/16	0.6/16	0.6/16	325	0/0.3	0/2	460

